




ROLL OFF CABLES

H-D extra improved plow steel rope with a special H-D mechanical thimble splice and fitting if necessary.



THREADED SWAGE STUDS

For any special application, with any thread specification



HAND SPLICED SLINGS

For those special applications where a mechanical splice can not be used.



CABLE LAID SLINGS

Extra flexibility is obtained by using a special multi-wire galvanized wire rope.



DIA.		ROPE CONSTRUCTION	WORKING LOAD LIMIT*					
in.	mm		VERTICAL		CHOKER		VERTICAL BASKET	
			Tons	metric tons	Tons	metric tons	Tons	metric tons
3/8	9.5	7 X 7 X 7	1.1	1.0	.74	.67	2.2	2.0
1/2	12.7	7 X 7 X 7	1.9	1.7	1.3	1.2	3.7	3.4
5/8	15.9	7 X 7 X 7	2.8	2.5	1.9	1.7	5.5	5.0
3/4	19.0	7 X 7 X 19	4.1	3.7	2.8	2.5	8.1	7.3
7/8	22.2	7 X 7 X 19	5.4	4.9	3.7	3.4	11	10
1	25.4	7 X 7 X 19	6.9	6.3	4.7	4.3	14	13

*WARNING: Never exceed working load limit.
Design factor 5:1 ASME B30.9 Specification .

For any special lift or sling consult your BISON representative.

TIRFOR CABLE

Special non preformed wire rope with hook & tapered end for use with TIRFOR.

