



## MALLEABLE WIRE ROPE CLIPS

G 426



CLIP & ROPE SIZE (INCHES)	MINIMUM NUMBER OF CLIPS REQUIRED
1/8	3
3/16	3
1/4	3
5/16	3
3/8	3
7/16	4
1/2	4
9/16	4
5/8	4
3/4	5
7/8	5
1	6
1 1/8	7

**\*WARNING:** Malleable rope clips are not designed for overhead lifting. Malleable rope clips are to be used for light duty, non-critical applications only. Typical uses include guard lines and fencing. Do not use malleable wire rope clips for critical or lifting applications.

## WIRE ROPE CLIPS

### FIST GRIP® CLIPS

- Bolts are an integral part of the saddle, with nuts on opposite sides of the clip, enabling the operator to swing his wrench in a full arc for fast installation.
- The "Fist Grip" clip is easily installed since its two parts are identical.
- Forged steel, galvanized.
- Standard heavy hex nuts.

#### IMPORTANT

Read Fist Grip Clip application booklet to insure clips perform to their maximum efficiency rating. Fist Grip Clip application booklets are available from HERCULES. Fist Grip wire clips meet or exceed requirements of Federal Specification FF-C-450 Type III, Class 1

® Registered trademark of "Crosby"

ROPE SIZE (in.)	DIMENSIONS IN INCHES										WEIGHT PER 100 (lbs.)
	A	B	C	D	E	G	L	M	N		
3/16 - 1/4	.25	1.25	.34	.94	.38	1.28	1.63	.69	1.47	18	
5/16	.31	1.34	.44	1.06	.38	1.47	1.94	.69	1.56	28	
3/8	.38	1.59	.50	1.06	.44	1.81	2.38	.75	1.88	40	
7/16 - 1/2	.50	1.88	.56	1.25	.50	2.19	2.75	.88	2.19	70	
9/16 - 5/8	.63	2.28	.69	1.50	.63	2.69	3.50	1.06	2.63	100	
3/4	.75	2.69	.88	1.81	.75	2.94	3.75	1.25	3.06	175	
7/8	.88	2.97	.97	2.13	.75	3.31	4.13	1.25	3.14	225	
1	1.00	3.06	1.19	2.25	.75	3.72	4.63	1.25	3.53	300	
1 1/8	1.13	3.44	1.28	2.38	.88	4.19	5.25	1.44	3.91	400	
1 1/4	1.25	3.56	1.34	2.50	.88	4.25	5.25	1.44	4.03	400	
1 3/8 - 1 1/2	1.50	4.13	1.56	3.00	1.00	5.56	7.00	1.63	4.66	700	

G 429

