



SHORT LEG STRUCTURAL "GX" CLAMP

This versatile clamp is a variation of the popular "GX" style. It is designed for a secure bite on small or odd-shaped, wide-flanged beams. A spring loaded cam is standard on all models. The clamps are designed to be used with the short leg under the plate when lifting the plate from the horizontal to the vertical position. Replacement parts are same as for the standard "GX" clamps.

| CAT. no. | WORKING LOAD LIMIT* Tons/kgs | GRIP RANGE in./mm | DIMENSIONS IN INCHES | | | | | | | | | | WEIGHT lbs. EACH |
|----------|---------------------------------|----------------------|----------------------|---------|--------|---------|--------|--------|--------|---------|---------|----------------|------------------------|
| | | | A | B | C | D | E | F | G | H | I | THICK- NESS | |
| 642-3100 | 1/2 / 454 | 1/16 - 5/8 / 1-16 | 4 | 9 1/2 | 2 1/8 | 2 5/8 | 2 | 4 1/16 | 2 7/8 | 1 3/8 | 4 3/4 | 1 3/4 | 4 1/4 |
| 642-3105 | 1 / 907 | 1/16 - 3/4 / 1-19 | 4 3/4 | 11 5/16 | 2 5/8 | 3 1/16 | 2 1/16 | 4 7/8 | 3 9/16 | 1 21/32 | 5 13/16 | 2 1/8 | 7 1/4 |
| 642-3108 | 2 / 1814 | 1/16-7/8 / 1-22 | 5 1/8 | 12 1/8 | 2 5/8 | 3 5/16 | 2 1/4 | 5 | 3 9/16 | 1 5/8 | 5 15/16 | 2 3/8 | 8 3/4 |
| 642-3110 | 3 / 2722 | 1/16 - 1 / 1-25 | 6 | 15 1/16 | 3 7/16 | 3 13/16 | 3 | 6 9/16 | 4 3/16 | 2 | 7 5/16 | 2 3/4 | 17 3/4 |

*WARNING : Never exceed working load limit.

DRAG CLAMP "GX" STYLE

With a heavy plate welded to its bottom edge, this clamp is ideal for dragging plates or heavy objects.

| CAT. no. | WORKING LOAD LIMIT* | | GRIP RANGE | | WEIGHT lbs. EACH |
|----------|---------------------|------|------------|--------|---------------------|
| | Tons | kgs | in. | mm | |
| 642-3300 | 1/2 | 454 | 1/16 - 5/8 | 1 - 16 | 5 |
| 642-3305 | 1 | 907 | 1/16 - 3/4 | 1 - 19 | 11 |
| 642-3310 | 3 | 2722 | 1/16 - 1 | 1 - 25 | 23 |

*WARNING : Never exceed working load limit. See "GX" Clamps for replacement parts.



SHARP LEG CLAMP, "GX" STYLE

This is a variation of the standard model "GX" clamp designed to lift stacked plates from horizontal to vertical positions. The long sharp leg can be driven between the top two plates to fully engage the clamp.



| CAT. no. | WORKING LOAD LIMIT* | | GRIP RANGE | | WEIGHT lbs. EACH |
|----------|---------------------|------|------------|--------|---------------------|
| | Tons | kgs | in. | mm | |
| 642-3500 | 1/2 | 454 | 1/16 - 5/8 | 1 - 16 | 5 |
| 642-3505 | 1 | 907 | 1/16 - 3/4 | 1 - 19 | 12 |
| 642-3510 | 3 | 2722 | 1/16 - 1 | 1 - 25 | 26 |

* WARNING : Never exceed working load limit. See "GX" Clamps for replacement parts.